

REED

Model R9200

Microwave
Leakage
Detector



**Instruction
Manual**

www.reedinstruments.com

REED Instruments

1-877-849-2127 | info@reedinstruments.com | www.reedinstruments.com

Features

- Detects very low levels of microwave leakage
- Quick response and high accuracy
- Designed for one-handed operation
- Audible (beep) and visual (flashing LED) alarms at 5 mW/cm²
- 4-digit, backlit LCD display
- Max hold function and low battery indicator
- Zero button for quick adjustment
- Includes soft carrying case and batteries

Specifications

Measuring Range:	0 to 9.99 mW/cm ²
Accuracy:	±1mW/cm ²
Resolution:	0.01 mW/cm ²
Operating Frequency:	2.4GHz
Display:	4-digit LCD
Backlit Display:	Yes
Alarm:	Audible (buzzer) and Visual (LED Light)
Alarm Limit:	5 mW/cm ²
Max Hold:	Yes
Zero Button:	Yes
Response Time:	2x per second
Power Supply:	9V Battery
Low Battery Indicator:	Yes
Product Certifications:	CE
Operating Temperature:	32 to 122°F (0 to 50°C)
Storage Temperature:	14 to 140°F (-10 to 60°C)
Operating Humidity Range:	10 to 90%
Dimensions:	6.3 x 2.4 x 1.7" (160 x 60 x 42 mm)
Weight:	5.3 oz (151 g)



www.reedinstruments.com

2

REED Instruments

1-877-849-2127 | info@reedinstruments.com | www.reedinstruments.com

Operating Instructions

1. Install the 9V battery.
2. Press the power button.
3. Press and hold the light/zero button to adjust to zero.
4. Take measurements.
5. Press the power button to turn the instrument off.

For service or information on this or any other REED product, contact REED Instruments at info@reedinstruments.com.



www.reedinstruments.com

3

REED Instruments

1-877-849-2127 | info@reedinstruments.com | www.reedinstruments.com

Notes _____

