

REED

THE RIGHT SOURCE THE RIGHT SOLUTIONS

COATING THICKNESS GAUGE

TECHNICAL DATA

FEATURES

- Measure the thickness of non-magnetic coatings on magnetic or non-magnetic metal substrates
- Choice of remote probe; F probe measures the thickness of non-magnetic coatings on magnetic metal substrates; N probe measures the thickness of non-magnetic coatings on non-magnetic metal substrates
- Automatic probe recognition
- Automatic calibration
- Large, easy-to-read LCD provides exact readings without guessing or errors
- $\mu\text{m}/\text{mil}$ conversion switch
- Includes hard carrying case and batteries

SPECIFICATIONS

Measuring Range: 0 to 1000 μm , 0 to 40 mil

Resolution: 0.1 μm

Accuracy: ± 1 to 3% or 2 μm , whichever is greater

Sampling Time: 1 second

Power Supply: 4 x 1.5V "AA" batteries

Dimensions: 6.3 x 2.7 x 1.25" (161 x 69 x 32mm)

Weight: 9 oz (260g)

ORDERING INFORMATION

CM-8822..... Coating Thickness Gauge

CM-8822FPROBE..... Ferrous Probe

CM-8822NPROBE..... Non-ferrous Probe

CERTICTG1.... Accredited Calibration Certificate



**Contact us at 1-800-561-8187
or info@reedinstruments.com**

www.reedinstruments.com

