

## Touchscreen Hand-Held Indicator



---

## Specifications

**Ambient Operating Temperature Conditions:** 0 to 122F (-18 to 50C)

**Approvals:** CE

**Cable Length:** 5ft (5ft)

**Calibration Point/s Checked:** N100, N300, N400

**Digital Display:** Transflexive Display

**Dimensions:** 5.7 x 2.7 x 1inch (14.4 x 6.8 x 2.7cm)

**Display Resolution:** 0.1° resolution to 999.9; 1° resolution above 1000

**Display Update Rate:** 1 per second

**Power Source:** 9V battery

**Response Time:** 10 seconds for full scale

**Temperature Accuracy:** +/-1.8F from -22 to 122F 3.8F (+/-1C from -30 to 50C 2.1C)

**Temperature Range:** -200 to 1999F (-128 to 1093C)

**Temperature Sensor Type:** K-Thermocouple

## Calibrations

**N100** 1-Point NIST Traceable Calibration

**N300** 3-Point NIST Traceable Calibration

**N400** 3-Point Ultima NIST A2LA Accredited Calibration

---

## Accessories



**A203 - Temperature Probe**  
6" (15cm) High Temperature Immersion Probe



**N520 - Certificate of Validation**  
Certificate of Validation