

TPT220

Voltage Tester



- AC and DC voltage from 6 to 1000 V
- Resistance / Continuity (acoustically)
- RCD function test
- Two pole phase sequence indication
- LCD display
- CAT IV 1000 V rating

DESCRIPTION

The Megger TPT220 voltage tester provides electricians and electrical engineers with voltage indication but has additional functions that make the instrument truly versatile.

The TPT220 features an LCD display that provides AC and DC voltage measurement from 6 to 1000 volts, in addition, a continuity / resistance function ranging from 0 to 2 k Ω . Continuity and voltage measurements greater than 35 V are accompanied by an acoustic sounder.

The display has a back light with an ambient light sensor that will illuminate the display in poorly lit environments. A low battery indicator, continuity data hold function and a torch lamp are also provided.

The unit has an RCD / FI test function that allows simple testing of 30 mA RCDs, RCBOs and safety breakers.

A test between phase and earth on a circuit protected by an RCD, RCBO and Safety Breaker will not trip these devices.

The phase sequence indication feature is simplified which avoids the typical crossing of the test probes adopted by many 2 pole testers.

With safety in mind, the TPT220 is CATIV 1000 V rated with an IP65 rated strong body that provides easy and comfortable grip. GS38 shrouds are provided as standard.

The unit has a feature that will warn the operator of dangerous test voltages should the batteries become exhausted.

FEATURES

- On / Off switch
- Exhausted battery warning indicator
- Spare GS38 tips included
- Auto power off

APPLICATION

Although this tester is primarily for testing in electrical installations the unit can be useful for a wide number of applications. The TPT220 can be utilised for testing auto electrical, fire alarm systems and telecom.

SPECIFICATIONS

Display	Optical 3 1/2 digit, LCD
Operating panel	RCD button, ON/OFF button, D-Hold button
Voltage range	6 to 1000 V
Accuracy	1.5% ±3 digits
Frequency (ACV)	40 to 400 Hz
Resistance/Continuity test	0 - 2000 Ω
Accuracy	5% ±5 digits
Phase indication	>100 V AC
Switchable load	Is <0.3 A ED (DT) = 30 sec.
Operating frequency	0 – 400 Hz
Torch	Ultra bright LED
Power Supply	2 x 1.5 V batteries type AAA LR03

Dimensions

70 mm (W) x 238 mm (H) x 30 mm (D)

Weight

200 g

Environmental

Operating temperature -10 °C - +55 °C

Humidity 96% Rh

Ingress protection IP65

Safety

CAT IV 1000 V

Compliance

TÜV, GS IEC/EN 61243-3 (DIN VDE 0628-401)

ORDERING INFORMATION

Item (Qty)	Cat. No.
TPT220 voltage tester CAT IV 1000 V	1001-615
Included accessories	
4 x GS38 tips	
Optional accessories	
MPU690 Proving unit	1001-561
GS38 tips (pack of 10)	1001-896

UK
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
F +44 (0) 1304 207342
UKsales@megger.com

UNITED STATES
4271 Bronze Way
Dallas TX 75237-1019 USA
T 800 723 2861 (USA only)
T +1 214 333 3201
F +1 214 331 7399
USsales@megger.com

OTHER TECHNICAL SALES OFFICES
Valley Forge USA, College Station USA,
Sydney AUSTRALIA, Täby SWEDEN, Ontario
CANADA, Trappes FRANCE, Oberursel
GERMANY, Aargau SWITZERLAND, Kingdom
of SAUDI ARABIA, Mumbai INDIA, Johannesburg
SOUTH AFRICA, Chonburi THAILAND

CERTIFICATION ISO
Registered to ISO 9001:2008 Cert. no. Q 09250
Registered to ISO 14001:2004 Cert. no. EMS 61597

TPT220_DS_en_V01
www.megger.com
Megger is a registered trademark