

Part No.

QTHA-KIT3

(1) 3' outlet hose with brass Quick-test ends, (1) QTHA-2MB0 1/4" Male NPT adapter, brass

A replacement hose and process connection helps reduce down-time due to not having the right accessories.



QTHA-KIT3

Included Items

- 1/4" Male NPT adapter, brass - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Quick-test hose, 3ft long - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)

Specs/Attributes

Max Pressure	5000 PSI / 350 bar / 35 MPa
Materials	Brass
Seal Materials	Buna-N
Country of origin	USA
Number of Adapters	1
Number of Hoses	1

1/4" Male NPT adapter, brass QTHA-2MB0

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm

1/4" Male NPT adapter, brass QTHA-2MB0

Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)

Quick-test hose, 3ft long QTQT-HOS-3ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	3ft / 0.91 m
Inner Diameter	0.08 In / 3.00 mm
Length	3 ft / 92 cm
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT