

Part No.

QTHA-2MS0-B341T03-QD

Cylinder adapter, BS341 TYPE 3 - Quick-connect x 1/4" Male NPT adapter, S.S.

Connect to any BS 341 Type 3 valve on high pressure compressed gas cylinders. BS 341 is a UK standard.



QTHA-2MS0-B341T03-QD

Specs/Attributes

| | |
|---------------------------|---|
| Certifications | BS 341 Type 3 (United Kingdom) |
| Country of origin | USA |
| Materials | Stainless Steel |
| Max Operating Temperature | 225 °F / 105 °C |
| Max Pressure | 5000 PSI / 350 bar / 35 MPa |
| Media Compatibility | Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water |
| Min Operating Temperature | 0 °F / -18 °C |
| Seal Materials | Buna-N, Urethane |
| Connector End 1 | Type 3 Male BS 341 |
| Connector End 2 | 1/4" Male NPT (ASME B1.20.1) |
| Weight | 11.18 oz / 315 grams |
| Dimensions | H: 4.25 in (10.8 cm) x W: 1.45 in (3.68 cm) x D: 1.45 in (3.68 cm) |