

Part No.

# QTHA-KIT1

Quick-test BSPP fitting kit - 1/8" MBSPP, 1/4" MBSPP, 1/8" FBSPP, 1/4" FBSPP, brass

Connect to Male or Female BSPP gauges, hand pumps, pressure calibrators or transmitters



QTHA-KIT1

## Included Items

- 1/8" Male BSPP adapter, brass - G 1/8" male BSPP (ISO 228/1) x male Quick-test, no check-valve, brass (QTHA-1MB0-RS)
- G 1/8" female BSPP adapter, brass - G 1/8" female BSPP (ISO 228/1) x male Quick-test, no check-valve, brass (QTHA-1FB0-RG)
- 1/4" male BSPP adapter, brass - G 1/4" male BSPP (ISO 228/1) x male Quick-test, no check-valve, brass (QTHA-2MB0-RS)
- G 1/4" female BSPP adapter, Brass - G 1/4" female BSPP (ISO 228/1) x male Quick-test, no check-valve, brass (QTHA-2FB0-RG)

## Specs/Attributes

Max Pressure	5000 PSI / 350 bar / 35 MPa
Materials	Brass
Seal Materials	Buna-N
Number of Adapters	4
Number of Hoses	0
Country of origin	USA

### 1/8" Male BSPP adapter, brass QTHA-1MB0-RS

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm

### 1/8" Male BSPP adapter, brass QTHA-1MB0-RS

Connector End 1	G 1/8 Male BSPP (ISO 228)
Connector End 2	Male Quick-test
Dimensions	H: 1 in (2.54 cm) x W: 0.56 in (1.42 cm)

### G 1/8" female BSPP adapter, brass QTHA-1FB0-RG

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Wrench Size	5/8 In 16 mm
Connector End 1	G 1/8 Female BSPP (ISO 228)
Connector End 2	Male Quick-test
Dimensions	H: 1.1 in (2.79 cm) x W: 0.63 in (1.6 cm)

### 1/4" male BSPP adapter, brass QTHA-2MB0-RS

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	3/4 In 19 mm
Connector End 1	G 1/4 Male BSPP (ISO 228)
Connector End 2	Male Quick-test
Dimensions	H: 1.25 in (3.18 cm) x W: 0.75 in (1.91 cm)

### G 1/4" female BSPP adapter, Brass QTHA-2FB0-RG

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa

**G 1/4" female BSPP adapter, Brass** QTHA-2FB0-RG

Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Wrench Size	3/4 In 19 mm
Connector End 1	G 1/4 Female BSPP (ISO 228)
Connector End 2	Male Quick-test
Dimensions	H: 1.12 in (2.84 cm) x W: 0.75 in (1.91 cm)