

Part No.

QTHA-KIT2

Quick-test BSPP fitting kit - 1/8" MBSPT, 1/4" MNSPT, 1/8" FBSPT, 1/4" FBSPT, brass

Connect to BSPT taper thread pressure gauges, transmitters and switches in the field



QTHA-KIT2

Included Items

- 1/8" male BSPT adapter, brass - 1/8" male BSPT (ISO 7/1) x male Quick-test, no check-valve, brass (QTHA-1MB0-RT)
- 1/8" female BSPT adapter, brass - 1/8" female BSPT (ISO 7/1) x male Quick-test, no check-valve, brass (QTHA-1FB0-RT)
- 1/4" male BSPT adapter, brass - 1/4" male BSPT (ISO 7/1) x male Quick-test, no check-valve, brass (QTHA-2MB0-RT)
- 1/4" female BSPT adapter, brass - 1/4" female BSPT (ISO 7/1) x male Quick-test, no check-valve, brass (QTHA-2FB0-RT)

Specs/Attributes

Max Pressure	5000 PSI / 350 bar / 35 MPa
Materials	Brass
Seal Materials	Buna-N
Country of origin	USA
Number of Adapters	4
Number of Hoses	0

1/8" male BSPT adapter, brass QTHA-1MB0-RT

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm

1/8" male BSPT adapter, brass QTHA-1MB0-RT

Connector End 1	1/8" Male BSPT (ISO 7)
Connector End 2	Male Quick-test
Dimensions	H: 1.2 in (3.05 cm) x W: 0.56 in (1.42 cm)

1/8" female BSPT adapter, brass QTHA-1FB0-RT

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	5/8 In 16 mm
Connector End 1	1/8" Female BSPT (ISO 7)
Connector End 2	Male Quick-test
Dimensions	H: 0.98 in (2.49 cm) x W: 0.63 in (1.6 cm)

1/4" male BSPT adapter, brass QTHA-2MB0-RT

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male BSPT (ISO 7)
Connector End 2	Male Quick-test
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)

1/4" female BSPT adapter, brass QTHA-2FB0-RT

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa

1/4" female BSPT adapter, brass QTHA-2FB0-RT

Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	3/4 In 19 mm
Connector End 1	1/4" Female BSPT (ISO 7)
Connector End 2	Male Quick-test
Dimensions	H: 1.13 in (2.87 cm) x W: 0.75 in (1.91 cm)