

Part No.

# QTHA-KIT6-6ft

Quick-test hose kit - (2) 6 ft hoses, (2) 1/8" MNPT, (2) 1/4" MNPT adapters, brass

Kits take the guesswork out of selecting adapters by providing a selection of the most popular combinations of hoses and adapters



QTHA-KIT6-6ft

## Included Items

- Process Connection 1 - 1/8" male NPT x male Quick-test, no check-valve, brass (QTHA-1MB0)
- Process Connection 2 - 1/8" male NPT x male Quick-test, no check-valve, brass (QTHA-1MB0)
- Process Connection 3 - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Hose 1 - Quick-test 6900 psi hose, brass hose ends, 6 ft (1.83 m) long (QTQT-HOS-6ft)
- Hose 2 - Quick-test 6900 psi hose, brass hose ends, 6 ft (1.83 m) long (QTQT-HOS-6ft)
- Process Connection 4 - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)

## Specs/Attributes

Materials	Brass
Seal Materials	Buna-N
Number of Adapters	4
Number of Hoses	2
Max Pressure	5000 PSI / 350 bar / 35 MPa
Country of origin	USA

## Process Connection 1 QTHA-1MB0

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa

### Process Connection 1 QTHA-1MB0

Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/8" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Dimensions	H: 1.2 in (3.05 cm) x W: 0.56 in (1.42 cm)

### Process Connection 2 QTHA-1MB0

Country of origin	USA
Has Check Valve	No
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/8" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Dimensions	H: 1.2 in (3.05 cm) x W: 0.56 in (1.42 cm)

### Process Connection 3 QTHA-2MB0

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA
Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)

### Hose 1 QTQT-HOS-6ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	6 ft / 1.83 m
Inner Diameter	0.08 In / 3.00 mm
Length	6 ft / 2.00 m
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT

### Hose 2 QTQT-HOS-6ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA
Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	6 ft / 1.83 m
Inner Diameter	0.08 In / 3.00 mm
Length	6 ft / 2.00 m
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT

### Process Connection 4 QTHA-2MB0

Burst Pressure	20000 PSI / 1380 bar / 140 MPa
Country of origin	USA

**Process Connection 4 QTHA-2MB0**

Materials	Brass
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Max Vacuum	0.00 InHg / 0.0 kPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N
Wrench Size	9/16 In 15 mm
Connector End 1	1/4" Male NPT (ASME B1.20.1)
Connector End 2	Male Quick-test
Dimensions	H: 1.29 in (3.28 cm) x W: 0.56 in (1.42 cm)