

Part No.

QTHA-KIT24

Ralston Quick-test™ NPT Gauge Connection Kit

Pressure gauge connection kit for manifold or pump mount for calibrating pressure gauges with NPT connections in the lab



QTHA-KIT24

Included Items

- Bag - Zippered bag to hold hose and adapters, nylon (SM-0084)
- 1/8" Female NPT - 1/8" female NPT Quick-connect x female Quick-test, no check-valve, S.S. (QTHA-1FSA-QD)
- 1/4" Female NPT - 1/4" female NPT Quick-connect x female Quicktest, no check valve, S.S. (QTHA-2FSA-QD)
- 1/2" Female NPT - 1/2" female NPT Quick-connect x female Quick-test, no check-valve, S.S. (QTHA-4FSA-QD)

Bag SM-0084

Materials	Zippered Nylon
Country of origin	USA
Weight	3 oz / 85 grams
Dimensions	H: 6 in (15.24 cm) x W: 1 in (2.54 cm) x D: 7 in (17.78 cm)

1/8" Female NPT QTHA-1FSA-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Connector End 1	1/8" Female NPT (ASME B1.20.1)
Connector End 2	Female Quick-test
Dimensions	H: 1.78 in (4.52 cm) x W: 0.79 in (2.01 cm)

1/4" Female NPT QTHA-2FSA-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Connector End 1	1/4" Female NPT (ASME B1.20.1)
Connector End 2	Female Quick-test
Dimensions	H: 1.94 in (4.93 cm) x W: 0.95 in (2.41 cm)

1/2" Female NPT QTHA-4FSA-QD

Country of origin	USA
Has Check Valve	No
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Teflon
Connector End 1	1/2" Female NPT (ASME B1.20.1)
Connector End 2	Female Quick-test
Dimensions	H: 1.95 in (4.95 cm) x W: 1.38 in (3.51 cm)