

Part No.

XTHA-KIT10

10,000 psi Hydraulic Pump with BSPP to Quick-test XT Conversion kit

Convert 10,000 psi hydraulic pump with BSPP connections to Ralston Quick-test XT



XTHA-KIT10

Included Items

- Reference Connection - G 3/8" male BSPP (ISO 228/1) x male Quick-test, no check-valve, with cap and chain, S.S. (XTFT-3MS0-RS)
- Bonded Seal - 3/8" male RS bonded seal ring, steel and Buna-N (QTHA-3BR-RS)
- Reference Connection - G 1/4" male BSPP (ISO 228/1) x male Quick-test XT, no check-valve, with cap and chain, S.S. (XTFT-2MS0-RS)
- Bonded Seal - 1/4" male RS bonded seal ring, steel and Buna-N (QTHA-2BR-RS)
- Hose - Quick-test XT 10,000 psi hose, S.S. hose ends, 3ft long (XTXT-HOS-3ft)
- Process Connection - 1/4" male NPT x male Quick-test XT Adapter, S.S. (XTHA-2MS0)

Specs/Attributes

| | |
|-----------------|-------------|
| Compatible with | Druck PV212 |
|-----------------|-------------|

Reference Connection XTFT-2MS0-RS

| | |
|---------------------------|--|
| Country of origin | USA |
| Has Check Valve | No |
| Materials | Stainless Steel |
| Max Operating Temperature | 225 °F / 105 °C |
| Max Pressure | 10000 PSI / 700 bar / 70 MPa |
| Min Operating Temperature | 0 °F / -18 °C |
| Seal Materials | Teflon, Viton |
| Wrench Size | 3/4 In 19 mm |
| Connector End 1 | Male Quick-test XT |
| Connector End 2 | G 1/4 Male BSPP (ISO 228) |
| Dimensions | H: 1.85 in (4.7 cm) x W: 0.75 in (1.91 cm) |

Bonded Seal QTHA-2BR-RS

| | |
|--------------|---------------------------------|
| Max Pressure | 0.00 PSI / 0.00 mbar / 0.00 kPa |
|--------------|---------------------------------|

Bonded Seal QTHA-2BR-RS

| | |
|-------------------|---------------------|
| Max Vacuum | 0.00 InHg / 0.0 kPa |
| Materials | Plated Steel |
| Seal Materials | Buna-N |
| Country of origin | USA |

Hose XTXT-HOS-3ft

| | |
|---------------------------|---|
| Burst Pressure | 40000 PSI / 2760 bar / 275 MPa |
| Color | Blue |
| Country of origin | USA |
| Fluid Media | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water |
| Inner Diameter | 0.08 In / 3.00 mm |
| Length | 3 ft / 92 cm |
| Materials | Reinforced Polyamide, Stainless Steel |
| Max Operating Temperature | 140 °F / 60 °C |
| Max Pressure | 10000 PSI / 700 bar / 70 MPa |
| Media Compatibility | Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water |
| Min Operating Temperature | -40 °F / -40 °C |
| Minimum Bend Radius | 1.00 In / 26 mm |
| Outer Diameter | 0.24 In / 7.00 mm |
| Type | XT |

Process Connection XTHA-2MSO

| | |
|---------------------------|--|
| Country of origin | USA |
| Has Check Valve | No |
| Materials | Stainless Steel |
| Max Operating Temperature | 225 °F / 105 °C |
| Max Pressure | 10000 PSI / 700 bar / 70 MPa |
| Min Operating Temperature | 0 °F / -18 °C |
| Seal Materials | Teflon, Viton |
| Wrench Size | 5/8 In 16 mm |
| Connector End 1 | 1/4" Male NPT (ASME B1.20.1) |
| Connector End 2 | Male Quick-test XT |
| Dimensions | H: 1.29 in (3.28 cm) x W: 0.63 in (1.6 cm) |