

tempmate.[®]

Take a look at the

tempmate.[®]-GS2





Main Technical Specifications tempmate.®-GS2 **T**

Battery type	All the variation available in Lithium and Non-Lithium option
Temperature Range	-30°C to +70°C
Temperature Accuracy	±0.3°C (-10°C ~ 45°C) , ±0.5°C (Other)
Temperature Resolution	0.1°C
Humidity Range	Available with the TH Model
Humidity Accuracy	Available with the TH Model
Resolution Humidity	Available with the TH Model
Ambient Light	0 to 10000lx / Accuracy 0.01lx
Resolution Ambient Light	0.01 lx
Local Data Storage Capacity	24,200 values for Temperature and Light
Shelf-Life	Lithium Battery devices : 12 months shelf life Non-Lithium Battery devices: 6 months shelf life
Battery	Lithium Battery: Li-ion Polymer Battery 2400mAh Non-Lithium Battery: Ni-MH Battery 2000 mAh
External Sensor	Available with the TE Model
Log Interval	User defined: 1 min. to 60 min. (10 min. as standard setting preconfigured)
Transmission Interval	User defined: 10 min. to 1440 min. (60 min. as standard setting preconfigured)
Recording Duration	Lithium Battery: 90 days (with standard log interval of 10 min. and transmission interval of 240 min.) Non Lithium Battery: 60 days (with standard log interval of 10 min. and transmission interval of 240 min.)
Startup Mode	By default start by button
Stop Mode	By default stop by button (optionally via the USB port or the cloud platform)
Start Delay	User defined: 0 min. to 1440 min. (No start delay as standard setting preconfigured)
Protection Class	IP65
Display	Multifunction Display
Dimensions	103 x 64 x 23 mm for Lithium and 103 x 64 x 30 mm for Non-Lithium
Weight	130 g for Lithium and 175 g for Non-Lithium
Certifications	CE, EN12830, EMC, RoHS, FCC
Validation Certificate	Available as PDF in the Cloud
Software	tempmate.®-Cloud
Report Generation	Readable in the Cloud and locally in the device through the USB 2.0 interface
Password Protection	Cloud Password Protection
Connectivity	LTE 4G cat 1 with 2G Fallback
Location	LBS - GSM Localization
Alarm Configuration	Up to 6 Alarm for temperature + up to 3 Alarm for light, Alarm Delay Programmable
Programmable	Via Cloud
Alarm Type	Single / Cumulative
Recommended Storage Temperature	+15°C to + 25°C
Case Material	Polycarbonate



Main Technical Specifications tempmate.®-GS2 **TH**

Battery type	All the variation available in Lithium and Non-Lithium option
Temperature Range	-30°C to +70°C
Temperature Accuracy	±0.3°C (-10°C ~ 45°C) , ±0.5°C (Other)
Temperature Resolution	0.1°C
Humidity Range	0% to 100%rH
Humidity Accuracy	±3% (20% ~ 80%) , ±5% (Other)
Resolution Humidity	1%
Ambient Light	0 to 10000lx / Accuracy 0.01lx
Resolution Ambient Light	0.01 lx
Local Data Storage Capacity	24,200 values for Temperature, Humidity and Light
Shelf-Life	Lithium Battery devices : 12 months shelf life Non-Lithium Battery devices: 6 months shelf life
Battery	Lithium Battery: Li-ion Polymer Battery 2400mAh Non-Lithium Battery: Ni-MH Battery 2000 mAh
External Sensor	Available with the TE Model
Log Interval	User defined: 1 min. to 60 min. (10 min. as standard setting preconfigured)
Transmission Interval	User defined: 10 min. to 1440 min. (60 min. as standard setting preconfigured)
Recording Duration	Lithium Battery: 90 days (with standard log interval of 10 min. and transmission interval of 240 min.) Non Lithium Battery: 60 days (with standard log interval of 10 min. and transmission interval of 240 min.)
Startup Mode	By default start by button
Stop Mode	By default stop by button (optionally via the USB port or the cloud platform)
Start Delay	User defined: 0 min. to 1440 min. (No start delay as standard setting preconfigured)
Protection Class	IP65
Display	Multifunction Display
Dimensions	103 x 64 x 23 mm for Lithium and 103 x 64 x 30 mm for Non-Lithium
Weight	130 g for Lithium and 175 g for Non-Lithium
Certifications	CE, EN12830, EMC, RoHS, FCC
Validation Certificate	Available as PDF in the Cloud
Software	tempmate.®-Cloud
Report Generation	Readable in the Cloud and locally in the device through the USB 2.0 interface
Password Protection	Cloud Password Protection
Connectivity	LTE 4G cat 1 with 2G Fallback
Location	LBS - GSM Localization
Alarm Configuration	Up to 6 Alarm for temperature + up to 6 Alarm for Humidity + up to 3 Alarm for light, Alarm Delay Programmable
Programmable	Via Cloud
Alarm Type	Single / Cumulative
Recommended Storage Temperature	+15°C to + 25°C
Case Material	Polycarbonate



Main Technical Specifications tempmate®-GS2 TE

Battery type	All the variation available in Lithium and Non-Lithium option
Temperature Range	-200°C to +100°C
Temperature Accuracy	±0.5°C (-10°C ~ 45°C) , ±1°C (Other)
Temperature Resolution	0.1°C
Humidity Range	Available with the TH Model
Humidity Accuracy	Available with the TH Model
Resolution Humidity	Available with the TH Model
Ambient Light	Available with the T and TH Model
Resolution Ambient Light	Available with the T and TH Model
Local Data Storage Capacity	24,200 values for Temperature
Shelf-Life	Lithium Battery devices : 12 months shelf life Non-Lithium Battery devices: 6 months shelf life
Battery	Lithium Battery: Li-ion Polymer Battery 2400mAh Non-Lithium Battery: Ni-MH Battery 2000 mAh
External Sensor	PT100 (cable length: 1m, length of probe is 6cm length, 4 mm in diameter, sensor tip: stainless steel)
Log Interval	User defined: 1 min. to 60 min. (10 min. as standard setting preconfigured)
Transmission Interval	User defined: 10 min. to 1440 min. (60 min. as standard setting preconfigured)
Recording Duration	Lithium Battery: 90 days (with standard log interval of 10 min. and transmission interval of 240 min.) Non Lithium Battery: 60 days (with standard log interval of 10 min. and transmission interval of 240 min.)
Startup Mode	By default start by button
Stop Mode	By default stop by button (optionally via the USB port or the cloud platform)
Start Delay	User defined: 0 min. to 1440 min. (No start delay as standard setting preconfigured)
Protection Class	IP65
Display	Multifunction Display
Dimensions	103 x 64 x 23 mm for Lithium and 103 x 64 x 30 mm for Non-Lithium
Weight	130 g for Lithium and 175 g for Non-Lithium
Certifications	CE, EN12830, EMC, RoHS, FCC
Validation Certificate	Available as PDF in the Cloud
Software	tempmate®-Cloud
Report Generation	Readable in the Cloud and locally in the device through the USB 2.0 interface
Password Protection	Cloud Password Protection
Connectivity	LTE 4G cat 1 with 2G Fallback
Location	LBS - GSM Localization
Alarm Configuration	Up to 6 Alarm for temperature, Alarm Delay Programmable
Programmable	Via Cloud
Alarm Type	Single / Cumulative
Recommended Storage Temperature	+15°C to + 25°C
Case Material	Polycarbonate


CONTACT INFORMATION



Do you have any questions? Please contact us - our experienced team will be happy to support you.

sales@tempmate.com

+49 7131 6354 0



tempmate GmbH
Wannenäckerstr. 41
74078 Heilbronn, Germany

Tel. +49-7131-6354-0
sales@tempmate.com
www.tempmate.com