

Part No.

QTHR-QT-50ft

Quick-test Hose Reel with 50ft Quick-test hose, brass hose ends

The Quick-test hose reel is an innovative solution for storing Ralston Quick-test hoses. It includes inlet and outlet ports, a brake and locking pin and multiple mounting options.



QTHR-QT-50ft

Included Items

- Hose Reel - Quick-test hose reel, empty (QTHR)
- Hose - Quick-test 6900 psi hose, brass hose ends, 50 ft (15.2 m) long (with hose reel) (QTQT-HOS-50ft)

Hose Reel QTHR

Burst Pressure	27600 PSI / 1905 bar / 190 MPa
Country of origin	USA
Materials	Anodized Aluminum, Brass, Powder Coated Steel, Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Seal Materials	Buna-N, Teflon
Weight	5.01 lbs / 2.27 kg
Dimensions	H: 9.5 in (24.13 cm) x W: 6.5 in (16.51 cm) x D: 11.5 in (29.21 cm)

Hose QTQT-HOS-50ft

Burst Pressure	27000 PSI / 1860 bar / 185 MPa
Color	Silver
Country of origin	USA

Hose QTQT-HOS-50ft

Fluid Media	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Hose Length	50 ft / 15.24 m
Inner Diameter	0.08 In / 3.00 mm
Length	50 ft / 16 m
Materials	Brass
Max Operating Temperature	140 °F / 60 °C
Max Pressure	6900 PSI / 475 bar / 48 MPa
Max Vacuum	-30.00 InHg / -101.6 kPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	-40 °F / -40 °C
Minimum Bend Radius	1.00 In / 26 mm
Outer Diameter	0.20 In / 6.00 mm
Type	QT