

## **SpotBot® 4G Plus Data Sheet**

## **Features**

Monitors and records impact, temperature, and humidity

Delivers near real-time alerts of conditions outside of the user defined thresholds

Alerts user of condition changes, incidents and location, via a secure cloud platform



## **Operating Key Specifications**

Measured Parameters	Impact, Temperature, Humidity and Location
Acceleration Range	3.5 – 100 G
Impact Frequency Filter	200 HZ
Temperature Range	-20°C to 60°C
Temperature Sample Rate	15 min to 24 hour (programmable)
Temperature Accuracy	±0.5°C
Humidity Range	10-90% RH
Humidity Accuracy	+/- 2% RH



Operating Key Specifications				
Alarm Messages	Immediate Notification	Immediate Notification		
Communication Technology	4G LTE-M, WiFi	4G LTE-M, WiFi		
Location	GPS, Nearest Cell Tower, Nearest W	GPS, Nearest Cell Tower, Nearest WiFi		
Dimensions	131 mm x 39 mm x 46 mm	131 mm x 39 mm x 46 mm		
Weight	189 gm	189 gm		
Mounting Options	Screw Mount / Adhesive / Magneti	Screw Mount / Adhesive / Magnetic Feet (Optional)		
Battery Type	Lithium Batter Pack	Lithium Batter Pack		
Battery Life	Reporting Intervals	Battery Life		
	1 hour	1 year		
	2 hours	2 years		
	4 hours	3.5 years		
	8 hours	5 years		
	12 hours	6 years		
	24 hours	7 years		

Rev: AMT 1/2023 2 www.spotsee.io