

Part No.

XTHA-FRS0

5/16"-24 UNF DP Transmitter x male Quick-test adapter, S.S.

Connect a Quick-test hose directly to a DP transmitter using the bleeder port when the transmitter is not mounted on a 3 or 5 valve manifold or when the manifold is not easily accessible.



XTHA-FRS0

Specs/Attributes

Compatible with	Rosemount 2051 Series DP Pressure Transmitters, Rosemount 3051 Series DP Pressure Transmitters, Yokogawa EJ series DP Pressure Transmitters, Anderson Greenwood M25 Block and Bleed Valves, Anderson Greenwood M251 Block and Bleed Valves, Foxboro (by Schneider Electric) IDP10, Foxboro (by Schneider Electric) IDP15, Foxboro (by Schneider Electric) IDP31, Foxboro (by Schneider Electric) IDP32, Foxboro (by Schneider Electric) IMV25
Country of origin	USA
Materials	Stainless Steel
Max Operating Temperature	140 °F / 60 °C
Max Pressure	10000 PSI / 700 bar / 70 MPa
Media Compatibility	Air, Inert Gas, Natural Gas, Petroleum Based Oil, Water
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Teflon, Viton
Wrench Size	9/16 In 15 mm