# MARATHON PRODUCTS

### Get Temperature & Humidity with Digital Display and USB Connectivity.

The **2C\TEMP-RH** multi-use data logger is a cost-effective solution for temperature monitoring of refrigerated vaccines, biological material, chemicals, pharmaceuticals and documenting the transportation of fruits and vegetables.

The 2C\TEMP-RH is our top-of-the-line data logger with dual 8k memory banks for temperature and humidity, 0.2°C midpoint temperature accuracy and resolution, and 3% midpoint humidi-

ty accuracy. This is a must have device if you work in a laboratory or metrology department.

**Functions include:** The convenient palm-sized design has a digital display that provides real-time viewing of all temperature and humidity information including min/max temperature and current humidity values. One quick look provides instant product acceptance or "quarantine" decisions. The internal thermistor accurately records time and temperatures for user-selectable readings in Celsius, or Fahrenheit. The internal software is user programmable and provides the following features: start time delay, sampling intervals, high and low alarm values, recording status, and measurement data.

**Visual Alarms:** All our data loggers have the ability to program alarm limits. Should the temperature reach levels outside these limits, the onboard red LED will light until reset by the user.

**Computer Ready:** Marathon's easy-to-use MaxiThermal software is available for Microsoft Windows XP, Vista, 7, 8 and 10. Simply plug the unit into a standard USB port on your PC. The MaxiThermal software and USB cable are available as separate accessory items.

## PRODUCTS, INC.

**Temperature Range** -29° C to +72° C

MARATHON PRODUCTS

1

2C\TEMP-RH

START

HR:MIN

19:30

alarm

MIN 65.6 DAYS

80.

-20° F to +160° F

### **Temperature Accuracy**

(NIST traceable) ±0.2°C from 0° to 10°C ±0.5°C at extremes

### Memory EEPROM, Storage

2 banks of 8k memory (7680 data points)

Humidity Range 0% to 100%


### **Humidity Accuracy**

(NIST tracable) ±3% from 25% to 75% ±5% at extremes

Don't ship without us!®

**MaxiThermal Software Highlights:** Easy-to-use software provides clear graphs. Report Summary & Statistics File Manager, Note Attachment, Zoom, Elapsed Time or Date/Time View, Recorded View, Celsius or Fahrenheit. Data can be exported to other Windows programs such as spreadsheets, word-processing or databases. Available for Windows XP, Vista, 7, 8 and 10.

An Enterprise Software version and 21CFR Part 11 Compliant Software are also available.



### Serialization:


This recorder is programmed at the factory with a unique serial number for positive tracking.

### Water-resistant Enclosure:

The product package is hermetically sealed to an IP66 rating.

### **Computer Download Capability:**

Recorded data can be easily downloaded via standard USB cable and Marathon's software.



### 2C\TEMP-RH Specifications SKU #7001

Memory EEPROM, Storage:	2 banks of 8k memory (approx. 8,000 measurements each)
Temperature Range:	-29° C to +72° C / -20° F to +160° F
Temperature Accuracy:	$\pm 0.2^\circ$ C from 0° to 10°C, $\pm 0.5^\circ$ C at extremes / $\pm 0.4^\circ$ F from 32° to 50°F, $\pm 0.9^\circ$ F at extremes
Temperature Resolution:	0.2°C / 0.4°F
Humidity Range:	0% to 100%
Humidity Accuracy:	$\pm 3\%$ from 25% to 75%, $\pm 5\%$ at extremes
Measurement Intervals:	Programmable from 2 seconds to months.
Temperature Sensor:	NIST-traceable Precision Thermistor
High and Low Alarm Limits:	LED indicator and audible alarm set by temperature and time
Internal Clock Accuracy:	Better than 2 minutes per month
Computer Interface:	Mini USB Connector
Internal Software Provides:	Start time, Interval, User description, Alarm values, Recording status, Measurement data, Software version, Serial number, Model type
Power Source:	One CR2450 Lithium Battery with a 2 year operating life and a 5 year shelf life.
Size:	9.0 cm (l) x 5.0 cm (w) x 2.8 cm (h) / 3.5 in.(l) x 1.96 in.(w) x .1.1 in.(h)
Weight:	85 g / 3 oz.
Warranty:	12 months
CE Certified:	CE Marking File

### Please call 1-510-562-6450

for more information or to place an order.

### www.marathonproducts.com

627 McCormick St., San Leandro, CA 94577 • sales@marathonproducts.com Specifications subject to change without prior notice.