

## 3" (76mm) Temperature Chart Recorder



### Specifications

**Ambient Operating RH Conditions :** 0-95% RH non-condensing

**Ambient Operating Temperature Conditions:** -22 to 122F (-30 to 50C)

**Battery Life (Avg):** 2 Years

**Calibration Options:** N100, N300, N400

**Channels:** CH1: Temperature

**Chart Rotation Speed:** 24 Hour or 7 Day

**Dimensions:** 2.2 x 3.7 x 3.7in

**Enclosure:** Black ABS and Polycarbonate

**IP Rating:** 20

**Included Accessories:** One AA Battery, Red Pen and Quick Start Guide. \*Charts sold separately.

**Mounting Options:** Free Standing, Wall Mounted or Suspended

**Power Source:** Battery; One AA Battery (User Replaceable)

**Response Time:** 11 Minutes to 63% of Full Scale (in air moving 5' per second)

**Temperature Accuracy:** +/-2F from 50 to 96F (+/-1C from 10 to 35C)

**Temperature Range:** 50 to 96F (10 to 35C)

**Temperature Sensor:** Precise spiral wound bi-metallic strip transducer

**Unit Weight:** 1 lb

**Units/Pkg:** 1

**Warranty:** 12-Month Limited

## Calibrations

**N100:** 1-Point NIST Traceable Calibration

**N300:** 3-Point NIST Traceable Calibration

**N400:** 3-Point Ultima NIST A2LA Accredited Calibration

---

## Accessories



**A715 - Wall Mount Case**  
Small Locking Wall Mount Case



**R006 - AA Battery**  
AA Alkaline Battery