



www.ralstoninst.com

Part No.

QTHA-CMS0-C580-QD

CGA 580 Quick-connect x Male Quick-test, no check valve, Stainless Steel

Connect to any CGA 580 cylinder valve without a wrench



QTHA-CMS0-C580-QD

Specs/Attributes

Certifications	CGA 580 (USA)
Country of origin	USA
Dimensions A	0.00 In / 0.00 mm
Dimensions B	0.00 In / 0.00 mm
Materials	Stainless Steel
Max Operating Temperature	225 °F / 105 °C
Max Pressure	5000 PSI / 350 bar / 35 MPa
Media Compatibility	Air, Alcohol, Antifreeze, Ethylene Glycol, Hydraulic Oil, Inert Gas, Mineral Oil, Natural Gas, Petroleum Based Oil, Skydrol, Windshield washer fluid, Transmission fluid, Light motor oil, Ralston Calibration Oil, Water
Min Operating Temperature	0 °F / -18 °C
Seal Materials	Buna-N, Urethane
Connector End 1	580 Male CGA 580
Connector End 2	Male Quick-test

Ralston Instruments Inc. | ralstoninst.com | Toll Free 800-347-6575 | Phone 440-564-1430 | Fax 440-564-1480

원문: Ralston Instruments QTHA-CMS0-C580-QD 데이터시트(영문) · 제조사 원문 자료입니다. 사양은 제조사 사정에 따라 변경될 수 있습니다.