

Beyond
the measure

FT 14154_EN

MAPPING KIT FOR CLIMATIC CHAMBERS

15 NOVA SPY D RED



Non-contractual picture

Presentation

With its metrological performance and fast response time, this mapping kit meets the requirements of FD X 15140 and IEC 60068 for mapping of climatic chambers via the mapping module of the JRI-MySirius platform..

Technical data

	MAPPING KIT 15 NOVA SPY D RED
Sensor type	PT100 on digital probes ; Ø2,2x30mm
Recorder	NOVA SPY DIGITAL RED - IP 68
Communication	Sans fil 2.4Ghz avec la passerelle LINK Ethernet ou Wifi
Dimensions	14,5 x 34,5 x 44 cm
T° range	de -40° à +80°C
Accuracy	± 0.15°C de -40°C à +80
Annual drift	°C <0,1°C
Resolution	0,01°C
Response time τ_{50}	~20 sec
Composition	15 Nova SPY D RED 1 Nano Link RED Ethernet + AC adapter and USB cable 1 Case - Options: 15 Green Digital Sensor Reference (or Short version) - Cellular 4G router 15 COFRAC calibration certificates - MySirius configuration import file

Assets

- Easy import into MySirius
- Low drift over time
- Interchangeable probes
- Wireless communication
- Direct installation in the enclosure with negligible impact on the load

Content

15 Nova SPY D
RED1 Link
Ethernet RED

1 case

Non-contractual document

JRI, Société par actions simplifiée au capital de 4 000 000 €
 Pôle logistique / 2 Rue de la Voivre / PA Technoland / BP 21 / 25490 FESCHES LE CHÂTEL / France
 SIRET 380 332 858 00030 - Tél : +33 (0)3 81 30 68 04 / Fax : +33 (0)3 81 30 60 99 / sales@group-mms.com
 Siège Social : 16 rue Louis Rameau / CS 90050 / 95872 BEZONS Cedex / France / APE 2651B / TVA FR 02 380 332 858

www.jri-mms.com

원문: JRI Mapping Kit 15 points Nova SPY Digital (without link) Mapping Kit 15 points Nova SPY Digital (without link) ·
 제조사 원문 자료입니다. 사양은 제조사 사정에 따라 변경될 수 있습니다.