

Beyond
the measure

Nova HUB

Transmission module



Photo for illustrative purposes only

DS 14190

Presentation

The Nova HUB provides reliable, continuous monitoring of critical data on the go. Its built-in battery and buffer memory ensure that information is collected and transmitted even in the event of a temporary network or power outage, thereby guaranteeing seamless traceability. Thanks to its advanced connectivity, the Nova HUB transmits all collected data in real time to the JRI-MySirius platform. Alerts are instantly sent via text message, email, or mobile notification for maximum responsiveness. Its built-in GPS geolocation enables precise tracking of vehicles and packages during transit.

Benefits

- Quick and easy setup
- Real-time monitoring and alarms
- Backup memory
- Compatible with the Nova and Nano SPY series

Technical Specifications

Operational Temperature Range	-10°C to +55°C
GPS Receiver	GNSS (GPS, GLONASS, Galileo, BeiDou, QZSS, SBAS compatible)
Rated voltage	5 / 12 / 24 V
Functions	Nova SPY data transmission (Temperature, humidity, door opening) GPS geolocation
Operational Tension	5 to 24 V
Input and Output Type	24GHz communication for receiving Nova SPY
Backup memory	20 hours of backup runtime at full load with a transmission frequency of every 15 minutes
Case	ABS UL94V-0 White
Battery	Lithium ION 2200 mA,
Dimensions	103 L x 70 W x 35 H mm
Weight	165g
Compliance with guidelines	RED/FCC/ISED

Geolocation

Highly sensitive GPS receiver that provides the geographic location of monitored products, packages, and vehicles. GPS data can be transmitted to MySirius at regular intervals or on an event-driven basis.

Geofencing

Automatic detection of entry into and exit from geographic areas (POI)

Real-time monitorings and alerts

The Nova HUB instantly sends a notification via MySirius if the temperature threshold is exceeded or when entering a POI. If the network is unavailable, the data is buffered for later transmission.

JRI, Société par actions simplifiée au capital de 4 000 000 €
Pôle logistique / 2 Rue de la Voivre / PA Technoland / BP 21 / 25490 FESCHES LE CHÂTEL / France
SIRET 380 332 858 00030 - Tél : +33 (0)3 81 30 68 04 / Fax : +33 (0)3 81 30 60 99 / sales@group-mms.com
Siège Social : 16 rue Louis Rameau / CS 90050 / 95872 BEZONS Cedex / France / APE 2651B / TVA FR 02 380 332 858

www.jri-mms.com

원문: JRI Nova HUB - Transmission module Nova HUB - Transmission module · 제조사 원문 자료입니다. 사양은 제조사 사정에 따라 변경될 수 있습니다.